

PXT-K Series Pressure Transmitters



Features

- 4-20 mA Output Signal
- Piezoresistive Pressure Transmitter
- Corrosion Resistant Construction
- High Stability

The **PXT-K Series** pressure transmitters are state-of-the-art instruments providing 4-20 mA output. Each Piezoresistive Pressure Transmitter contains a transducer comprised of a piezoresistive silicon chip mounted on a glass-metal feed-through header welded into a stainless steel housing and filled with silicone oil; the very thin laser-welded stainless steel isolation-diaphragm completes the front side. Media pressure is transferred from the stainless steel isolation-diaphragm, via the oil inside the cell, to the silicon measuring chip. This construction, combined with the advanced internal signal conditioning circuitry, results in a rugged instrument with extremely small temperature error and class-leading EMI/RFI resistance.

The enclosure and all wetted parts are made of 316L stainless steel to meet NACE MR01-75.

Applications: **PXT-K Series** Pressure Transmitters can be used in applications such as Compressors, Engines, Process Control, Liquid Level and Pumps.

Specifications

Operating Pressure Range: See the part number matrix on the reverse side.

Operating Temperature: -40 to 180°F (-40 to 82°C).

Compensated Temperature Range: -20 to 160°F (-29 to 71°C).

Physical Characteristics:

Process Connection: 1/4 NPT female with 7/8" Hex Nut.

Electrical Connection (PXT-K-XXX): 1/2" NPT Male Conduit connection with 60" long cable, vented

Enclosure: NEMA 4/IP65 or better

Body: 316L Stainless Steel. Meets NACE MR01-75.

Wetted Parts: 316L stainless steel

Environmental Effect (Humidity): No effect for 0-95%, Non-condensing

Mounting: Transmitter can be installed in any axis. Transmitter position has negligible affect on performance as long as it is perpendicular to the flow being monitored.

Shock Resistance: 1000g per IEC 60068-2-6 (Mechanical Shock)

Vibration Resistance: 20G per IEC 60068-2-6 (Vibration under resonance)

Wiring Protection: Protected against reverse polarity and short circuit, 48 VDC Maximum

Supply Voltage: 8 - 30 VDC (Typically 24 VDC)

Transmitter Output: 4-20mA, two wire configurations with load characteristics

Insulation: Greater than 10MΩ @ 300 VDC

Electromagnetic Compatibility (EMC): Standards; EN 61000-6-2:2005, EN 61000-6-3:2007, EN 61326-2-3:2006

Voltage Surge/Spike Protection: Protection against a 600 Volt spike per IEC 60-2

Shipping Weight: 6.5 ounces

Applicable Standards:

NACE MR0175 Compliant with the requirements

CSA (c/us): Class I / II / III, Div 1, Groups A-F T4
Class I / II / III, Div 2, Groups A-D,F,G T4

ATEX: IExU 10 ATEX 1124 X



II 1G Ex ia IIC T6-T4

II 3G Ex nA IIC T6

PXT and PXT-K Series Pressure Transmitter Cabling Identification

The PXT Series Pressure Transmitters have been changed. Previous pressure transmitters in this series were identified as **PXT Pressure Transmitters**. The newest version is the **PXT-K Series Pressure Transmitters**. Identification of electrical cable color is NOT interchangeable between the two series of pressure transmitters.

This document contains information to assist you in identifying the pressure transmitter unit you have and the correct electrical cable colors to avoid wiring mistakes.

PXT SERIES	PXT-K SERIES
 <p data-bbox="198 982 706 1218"> Indentations on the hex coupling for controlled locking. Product has a step-down between the transmitter body and hex coupling. </p>	 <p data-bbox="1120 1029 1437 1197"> No step-down between the body and the hex coupling. No indentations on the hex coupling. </p>

Cable Color	Connection	Cable Color	Connection
RED	POWER	RED	POWER
BLUE	SIGNAL	BLUE	N/A
BLACK	CASE GROUND	BLACK	SIGNAL
ORANGE, YELLOW, WHITE	N/A	ORANGE, YELLOW, WHITE	N/A
Installation Instructions	00-02-0475	Installation Manual	00-02-0840
Installation Diagram	05-08-0754	Installation Diagram	05-08-0763

ENOVATION CONTROLS GLOBAL HEADQUARTERS

5311 S 122ND EAST AVENUE
TULSA, OK 74146

ENOVATION CONTROLS – SAN ANTONIO OFFICE

5757 FARINON DRIVE
SAN ANTONIO, TX 78249

ENOVATION CONTROLS – HOUSTON OFFICE

105 RANDON DYER RD
ROSENBERG, TX 77471

FW MURPHY, LTD. – UNITED KINGDOM

CHURCH ROAD LAVERSTOCK
SALISBURY SP1 1QZ UK

MURPHY ECONTROL TECHNOLOGIES (HANGZHOU) CO, LTD.

77 23RD STREET
HANGZHOU ECONOMIC & TECHNOLOGICAL DEVELOPMENT AREA
HANGZHOU, ZHEJIANG 310018 CHINA

DOMESTIC SALES & SUPPORT**ECONTROL PRODUCTS**

PHONE: 210 495 9772
FAX: 210 495 9791
EMAIL: INFO@ECONTROLS.COM
WWW.ECONTROLS.COM

MURPHY PRODUCTS

PHONE: 918 317 4100
FAX: 918 317 4266
EMAIL: SALES@FWMURPHY.COM
WWW.FWMURPHY.COM

MURPHY CONTROL SYSTEMS & SERVICES

PHONE: 281 633 4500
FAX: 281 633 4588
EMAIL: CSS-SOLUTIONS@FWMURPHY.COM

MURPHY INDUSTRIAL PANEL DIVISION

PHONE: 918 317 4100
FAX: 918 317 4124
EMAIL: IPDSALES@FWMURPHY.COM

INTERNATIONAL SALES & SUPPORT**UNITED KINGDOM**

PHONE: +44 1722 410055
FAX: +44 1722 410088
EMAIL: SALES@FWMURPHY.CO.UK
WWW.FWMURPHY.CO.UK

CHINA

PHONE: +86 571 8788 6060
FAX: +86 571 8684 8878
EMAIL: APSALES@FWMURPHY.COM

LATIN AMERICA & CARIBBEAN

PHONE: 918 317 2500
EMAIL: LASALES@FWMURPHY.COM

SOUTH KOREA

PHONE: +82 70 7951 4100
EMAIL: SKOREASALES@FWMURPHY.COM

INDIA

PHONE: +91 91561 37633
EMAIL: INDIASALES@FWMURPHY.COM

ISO 9001
REGISTERED

USA (710,54) - ISO 9001:2008 FM 20221
UK (ROSENBERG) - ISO 9001:2008 FM 20221
UK (FW MURPHY) - ISO 9001:2008 FM 29422
CHINA - ISO 9001:2008 FM 52285
Registered Facilities

Printed in the USA